



# LUXAPOOL® CR

## (CHLORINATED RUBBER BASED SWIMMING POOL PAINT)

**Finish:** Satin Gloss  
**Colours:** Range of standard colours. (refer LUXAPOOL® colour card)  
- Special colours available on request for bulk large orders only.

**Recommended Uses:** Private & commercial swimming pools and ponds

**Features:**

- One pack (ready for use)
- Fast drying
- Economical & easily maintained
- U.V. Resistant
- Highly chemical resistant
- Excellent adhesion to well prepared surfaces.

**Performance Data:**

- Will not propagate fungus or algae growth.
- Extremely low water permeability
- Excellent chemical resistance.
- Time to between re-coats on well prepared surfaces would be approx. 3 - 4 years depending on wear & tear and colour used



# TECHNICAL DATA

**Coverage:** (Theoretical) 5 - 6m<sup>2</sup> / lt (depending on porosity and profile of surface.)

**Volume Solids:** 40 - 50% approx.(colour dependent)

**Drying Time:** Touch Dry..... 1 - 2 hours @ 20° C / 50% RH  
Re-coatable..... By Brush or Roller - 24hours @ 20° C /50% RH

**Thinners:** LUXAPOOL® CR thinners ONLY

**Application Equipment :** Brush and Roller

**Safety Data:** **Flammable:** store and use away naked flame or heat.  
- Wear rubber or PVC gloves when using / can cause an allergic reaction.  
- Provide good ventilation when applying.  
- Do not smoke or eat in the vicinity of coating.

**Packaging:** 4lt & 15lt Tins

### IMPORTANT NOTE / DISCLAIMER :

ALL MATERIALS ARE SUPPLIED TO COMMERCIAL & DOMESTIC CLIENTS STRICTLY UNDER THE FOLLOWING CONDITIONS - SINCE CONDITIONS OF USE AND THE COMPETENCE OF THE APPLICATOR ARE TOTALLY BEYOND OUR CONTROL, WE ASSUME NO RESPONSIBILITY OR LIABILITY IN CONNECTION WITH THE USE OF THE PRODUCT RELATIVE TO COVERAGE, OVERALL PERFORMANCE, LOSS OF INCOME OR INJURY. IF ANY FAILURE OR PROBLEM ARISE, D.P.J. COATING SYSTEMS PTY LTD ARE NOT OBLIGED BY LAW TO ATTEND ON SITE OR TO PROVIDE ANY REMEDY WHATSOEVER, AND IT WOULD BE YOUR RESPONSIBILITY TO PROVE THAT ANY FAILURE IS THE RESPONSIBILITY OF THE COATING MANUFACTURER.

